Amendments to the Specification

On page 3, after line 5, please insert the following new paragraph:

Figure 7A is a perspective view of a guide lock of the invention.

On page 3, after line 7, please insert the following new paragraph:

Figure 8A is a plan view of an alternative arrangement guide lock and cargo lock of the invention.

Please replace the paragraph beginning on page 5 at line 3, with the following amended paragraph:

Figure 2 is a perspective view of one embodiment of the vehicle side of the system. Figure 2 shows a rack 100 with a guide 110 in more detail. A guide lock 120 is shown in the bottom of the guide, though it is understood that the guide lock could be on one or both of the sidewalls 105, the bottom 108, or any combination of the bottom 108 or sidewalls 105 of the guide (Figures 8 and 8A). The guide lock is shown as a tab configuration, although the guide lock could be configured in any fashion, for example, as a loop 120' (Figure 7A), hole, hook or any locking engagement mechanism as will be obvious to those skilled in the art. The guides 110 shown in Figure 2 are shown as being attached to the top surface of the rack 100. This is but one exemplary embodiment of the invention and is not intended to be limiting. For example, the rack could be a collection of metal rods, a platform as shown, or any other cargo rack as is known in the art. The guides may be installed above the rack as shown, at the same level as the rack, below the rack, or at any configuration useful to the particular application. Figure 2 also shows the sidewalls 105, the retaining member 130, the sidewall holes 140, and the retaining member cable 160.